



METEOR

P80



SCAN ME



Excavator mounting ≤ 2.5 Tons

Reference	METEOR	Nbr of saw blades – knife plates / diameter (mm)	Cutting capacity (mm)	Cutting length (m)	Weight (kg) Without hitching	£
MP80.1700.17	P80 LAMIER 1700	1 saw blade / Ø700	Ø240/Ø25	0.70	60	£4,019

METEOR P80 :

* Chassis with a pierced plate, predisposed to receive the hitching bracket between the pruning equipment and the excavator
(Hitching NOT included)

* A Lamier support piece that can be rotated 90° to a horizontal axis, done manually

* Manual locking

* Cutting equipment **SINGLE BLADE 700 type** diameter **700mm**:

> Equipped with single blade diameter 700 mm - 80 Teeths - Thickness. 4mm

> Gear hydraulic motor 17 cm³

° Double rotation sense

° Without pressure limiter

° Flow and pressure required: **35 l/min at 180 bar**

° Rotation speed: 2000 RPM

> Drive : Direct transmission from the engine

* A set of connectors :

> Female ¾ gaz for engine supply

> Mâle 12L for the drain

* Tools to maintain and to change the cutting equipment

* Operation and maintenance manual for the pruning equipment and spare parts manual

Does not include:

* Hitching bracket between the pruning equipment and the excavator

* Flow regulator and pressure limiter

* Safety valve

* Flexibles kit between the excavator and the motor

* Hydraulic couplers

Hydraulic prerequisites on the excavator:

* Continuous hydraulic oil flow simple effect at the end of the boom of **35 l/min at 180 bar**

* This flow must be constant, regardless of the movements of the carrier, and at a forward speed less than 1 km/h

* Drain to direct return to tank (max. allowable pressure on the drain: 2.5 bar)

Prerequisites in cabin:

* A start up button for the Lamier

* An emergency stop button

* A command to activate the movement of the cylinder

Accessories		£
*KLP.45L.MBSP12	* Pressure limiter MANDATORY delivered, mounted (<i>imperative if pressure > pressure required</i>) NOTE: Only one direction of rotation in this case	£395
KCR.45L.MBSP12	Safety valve kit from 30 L to 60 L	£265
K3F.40L.02M	Flexibles kit 2 m (oil flow 40 L)	£222
Hitching bracket (connection between the cutting equipment and the excavator)		