



RELIABLE
CHIPPING

TP 175 TRACK - Remote c.



Infeed

| | |
|--------------------|--------------|
| Roller opening: | 175 x 191 mm |
| Number of rollers: | 2 |
| Roller position: | Horizontal |

Chipper type

| | |
|-------------------------------|--------------|
| Chipper type: | Disc chipper |
| Chipping angle: | 90° |
| TP OPTICUT: | Yes |
| TP TWIN DISC: | Yes |
| Number of knives: | 2 |
| Number of cuts per turn: | 2 |
| Woodchip size: | 4-10 mm |
| Rotorspeed: | 1750 r/min |
| Rotordiameter: | 599 mm |
| Rotorweight: | 69 kg |
| Transmission: | TP STARTER |
| Counter knife horizontal: | 1 turnable |
| Counter knife vertical: | 1 |
| Replacement of wearing plate: | No |
| Wearing plate: | Yes |
| TP CHIP KIT: | Option |

Spout System

| | |
|-----------------|----------|
| TP VARIO SPOUT: | Option |
| TP FIXED SPOUT: | Standard |

Stress control

| | |
|-----------------|---|
| Stress control: | Stress control system TP PILOT + with TP EASY CONTROL |
|-----------------|---|

Engine

| | |
|----------------------|------------------|
| Engine: | Kubota D1305-E4B |
| Fuel: | Diesel |
| Engine power: | 25 hp/18,5 kW |
| Number of cylinders: | 3 |
| Fuel consumption: | 3l/h |

Dimensions

| | |
|-------------------------------|----------------------|
| Length (transport/operation): | 2571 mm/3123 mm |
| Width: | 1150 - 1300 mm |
| Height (t/o) TP VARIO SPOUT: | 1900 mm/2049-2590 mm |
| Height (t/o) TP FIXED SPOUT: | 2049 mm |
| Weight: | 1150 kg |

Operation

| |
|-----------------|
| Remote Control: |
|-----------------|

TECHNICAL DRAWING

TP 175 TRACK

