



RELIABLE  
CHIPPING

## TP 165 MOBILE P



### Infeed

<b>Roller opening:</b>	175 x 191 mm
<b>Number of rollers:</b>	2
<b>Roller position:</b>	Horizontal

### Chipper type

<b>Chipper type:</b>	Disc chipper
<b>Chipping angle:</b>	90°
<b>TP OPTICUT: TP</b>	Yes
<b>TWIN DISC:</b>	Yes
<b>Number of knives:</b>	2
<b>Number of cuts per turn:</b>	2
<b>Woodchip size:</b>	4-12 mm
<b>Rotorspeed:</b>	1450 r/min
<b>Rotordiameter:</b>	599 mm
<b>Rotorweight:</b>	69kg
<b>Transmission:</b>	Clutch
<b>Counter knife horizontal:</b>	1 turnable
<b>Counter knife vertical:</b>	1
<b>Replacement of wearing plate:</b>	No
<b>Wearing plate:</b>	Yes
<b>TP CHIP KIT:</b>	Option

### Spout System

<b>TP VARIO SPOUT:</b>	Option
<b>TP FIXED SPOUT:</b>	Standard

### Stress control

<b>Stress control:</b>	TP PILOT+
------------------------	-----------

## Engine

**Engine:**

Kohler Pro CH 730, Honda GX 690  
or Honda GX630

**Fuel:**

Gasoline

**Engine power:**

23,5 hp/17 kW, 22 hp/16,5 kW or  
21HP

**Number of cylinders:**

2

**Fuel consumption:**

5l/h

## Dimensions

**Length (transport/operation):**

3515 mm/4013 mm

**Width:**

1416 mm

**Height (t/o) TP VARIO SPOUT:**

1750 mm/1965-2440mm

**Height (t/o) TP FIXED SPOUT:**

1995 mm

**Weight:**

680 kg

TECHNICAL DRAWING

TP 165 MOBILE

